RDWS-242 SF6 Trace Moisture Tester

RDWS-242 SF6 SF6 Trace Moisture Tester adopts reliable imported humidity sensor, which is the perfect combination of imported humidity sensor and digital circuit control technology. The instrument can measure accurately and reliably in full range, and has good long-term stability and good repeatability. It is



Website: www.hvtesters.com

not affected by dust particles and most chemicals, so that the measuring instrument can be used in various harsh industrial environments.

Product features

- 1. Portable design
- 2. Large Measuring Range
- 3. High Accuracy
- 4. LCD direct Display
- 5. Built-in Rechargeable Battery
- 6. Easy to Operate
- 7. Auto Drying System to Reduce measuring
- 8. Less time and the test gas consumption, and improve working efficiency.

Product specifications and technical parameters

Model	RDWS-242	
Dew Point	Measuring range	- 80 °C ~ +60 °C
	Measurement accuracy	±2°C@ -80~-60°C, ±1°C @ - 59~+20°C
	Measuring time	<4 min/Point
Measuring Flow	>1000 mL/min	

Pressure	≤1.0MPa	
Power Supply	AC 220V	
	Built in rechargeable battery	
Weight	3 kg	
Size	250mm×100mm×300mm	



Rui Du Mechanical and electrical (Shanghai) Co., Ltd



TEL: +86-021-68769756 Contact: Nico Zhou Position: Sales Manager

Email: sales@hvtesters.com
Website: www.hvtesters.com

Website: www.hvtesters.com

Mob/ WhatsApp: +86-136 6190 8522